

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 May 2004 (13.05.2004)

PCT

(10) International Publication Number
WO 2004/039614 A1

(51) International Patent Classification⁷:
F16D 3/223

B60F 3/00,

(74) Agent: BAIN SMITH, Timothy; Wickens Manor, Charing, Nr. Ashford, Kent TN27 0DT (GB).

(21) International Application Number:

PCT/GB2003/004752

(22) International Filing Date:

1 November 2003 (01.11.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0225492.8

1 November 2002 (01.11.2002)

GB

(71) Applicants (for all designated States except US): GIBBS TECHNOLOGIES LTD. [GB/GB]; Avenue Road, Nuneaton, Warwickshire CV11 4LY (GB). GIBBS TECHNOLOGIES LTD. [—/—]; La Motte Chambers, St. Helier, Jersey JE1 1BJ (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): ROYCROFT, Terence, James [NZ/NZ]; 135, Manukau Heads Road, Awhitu, Waiuku RD4 (NZ).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: AMPHIBIOUS VEHICLE WHEEL TRANSMISSION ARRANGEMENT



(57) Abstract: An amphibious vehicle (10) has a retractable suspension system. The transmission to a driven wheel comprises a plunging CV joint (7) at the outer or wheel end of driveshaft (5), and a fixed CV joint (3A) at the inner or differential end of the driveshaft. The fixed joint at the inner end of the shaft allows wheel movement between a lowered position allowing increased ground clearance, through a normal road use position, to a retracted wheel position above the vehicle water line. At least one inner CV joint may incorporate a driveshaft decoupler (20); which may incorporate synchromesh. The vehicle may be a planing vehicle, with either a longitudinal or a mid-mounted transverse prime mover; which may be an internal combustion engine or a fuel cell powered electric motor.



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.